



Your Personal Connection

# Assortment heat shrink tubing in display

## Assortment heat shrink tubing in display

WKK offers a practical metal display which contains a wide range of thin- and dual-wall heat shrink tubing. The heat shrink tubing has a standard length of 1220 mm, is packed per type / size in a display box and can easily be taken out to be sold per piece or in small quantities. All bars will be delivered in black. Other colors can be delivered on request.



### Specifications types of heat shrink tubing

#### H-2(Z):

Thin-wall heat shrink tubing / flexible / flame retardant / 2:1

#### Features:

- Crosslinked Polyolefin
- Shrink ratio: 2:1
- Flame retardant
- General purpose
- High flexibility

#### Application:

- Operating temperature: -55 °C to +125 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +100 °C
- Longitudinal change: 0 ± 10% max.

#### Order information:

- Color: black
- Other colors are available on request: red, blue, yellow, green, white
- In lengths of 1220 mm

#### H-5(3X)-F:

Dual-wall heat shrink tubing / flexible / flame retardant / 3:1 / adhesive lined

#### Features:

- Crosslinked co-extruded adhesive lined Polyolefin
- Shrink ratio: 3:1
- Flame retardant
- Excellent sealing and insulation properties
- UV-resistant

#### Application:

- Operating temperature: -55 °C to +125 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +110 °C
- Longitudinal change: 0 ± 10% max.

#### Order information:

- Color: black
- In lengths of 1220 mm

### Content display

Type / Size	As supplied: inside diameter in mm (min.)	After recovery: inside diameter in mm (max.)	After recovery: wall thickness in mm (min.)	Number of pieces in display
H-2(Z) 2:1 2,4/1,2	2,4	1,2	0,44	50
H-2(Z) 2:1 3,2/1,6	3,2	1,6	0,44	50
H-2(Z) 2:1 4,8/2,4	4,8	2,4	0,51	25
H-2(Z) 2:1 6,4/3,2	6,4	3,2	0,56	25
H-2(Z) 2:1 9,5/4,8	9,5	4,8	0,56	10
H-2(Z) 2:1 12,7/6,4	12,7	6,4	0,65	10
H-5(3X)-F 3:1 3,0/1,0	3,0	1,0	1,00	50
H-5(3X)-F 3:1 4,8/1,5	4,8	1,5	1,00	25
H-5(3X)-F 3:1 6,0/2,0	6,0	2,0	1,00	25
H-5(3X)-F 3:1 9,0/3,0	9,0	3,0	1,40	10
H-5(3X)-F 3:1 12,0/4,0	12,0	4,0	1,60	10
H-5(3X)-F 3:1 19,0/6,0	19,0	6,0	2,15	5

To order a display or new heat shrink tubing bars, please see the order form on the other side



Your Personal Connection

# Assortment heat shrink tubing in display

## Order form

Company name : .....

Contact person : .....

E-mail address : .....

Phone number : .....



## Order display(s) with assortment heat shrink tubing

Order number of displays with assortment heat shrink tubing ..... piece(s)

## Order heat shrink tubing bars (1220 mm) to refill display(s)

Type / Size	Max. quantity which fits in the display box	Black	Red	Blue	Yellow	Green	White
H-2(Z) 2:1 2,4/1,2	50	..... x 50 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.
H-2(Z) 2:1 3,2/1,6	50	..... x 50 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.
H-2(Z) 2:1 4,8/2,4	25	..... x 25 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.
H-2(Z) 2:1 6,4/3,2	25	..... x 25 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.
H-2(Z) 2:1 9,5/4,8	10	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.
H-2(Z) 2:1 12,7/6,4	10	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.	..... x 10 pcs.

Type / Size	Max. quantity which fits in the display box	Black
H-5(3X)-F 3:1 3,0/1,0	50	..... x 50 pcs.
H-5(3X)-F 3:1 4,8/1,5	25	..... x 25 pcs.
H-5(3X)-F 3:1 6,0/2,0	25	..... x 25 pcs.
H-5(3X)-F 3:1 9,0/3,0	10	..... x 10 pcs.
H-5(3X)-F 3:1 12,0/4,0	10	..... x 10 pcs.
H-5(3X)-F 3:1 19,0/6,0	5	..... x 5 pcs.

Please send this order form to: [sales@wkk.nl](mailto:sales@wkk.nl)