

Assortments heat shrink tubing

Features:

- Crosslinked Polyolefin
- Shrink ratio: 2:1
- Flame retardant
- General purpose
- High flexibility

Application:

- Operating temperature: -55 °C to +125 °C
- Minimum shrink temperature: +70 °C
- Minimum full recovery temperature: +100 °C
- Longitudinal change: 0 ± 10% max.

Content assortment 1: 127 pcs H-2(Z) heat shrink tubing (mixed colors)

Type / Size	Length in mm	Quantity
H-2(Z) 1,6/0,8	35,0	30
H-2(Z) 2,4/1,2	35,0	25
H-2(Z) 3,2/1,6	35,0	20
H-2(Z) 4,8/2,4	35,0	20
H-2(Z) 6,4/3,2	75,0	16
H-2(Z) 9,5/4,8	75,0	8
H-2(Z) 12,7/6,4	100,0	8



Content assortment 2: 127 pcs H-2(Z) heat shrink tubing (black)

Type / Size	Length in mm	Quantity
H-2(Z) 1,6/0,8	35,0	30
H-2(Z) 2,4/1,2	35,0	25
H-2(Z) 3,2/1,6	35,0	20
H-2(Z) 4,8/2,4	35,0	20
H-2(Z) 6,4/3,2	75,0	16
H-2(Z) 9,5/4,8	75,0	8
H-2(Z) 12,7/6,4	100,0	8



Content assortment 3: 469 pcs H-2(Z) heat shrink tubing (black)

Type / Size	Length in mm	Quantity
H-2(Z) 2,4/1,2	35,0	124
H-2(Z) 3,2/1,6	35,0	100
H-2(Z) 4,8/2,4	35,0	80
H-2(Z) 6,4/3,2	35,0	60
H-2(Z) 9,5/4,8	70,0	65
H-2(Z) 12,7/6,4	70,0	15
H-2(Z) 16,0/8,0	100,0	15
H-2(Z) 19,0/9,5	70,0	5
H-2(Z) 25,4/12,7	70,0	5

